

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Silirub Color

Revision: 8/10/2014

Page 1 from 4

Reference nr DOP: 230010

Unique identification code of the product type:

Soudal Silirub Color

Intended use or uses of the construction product:

**Sealant for facade for interior and exterior application, intended for use in cold climate.
Sealant used for sealing glazing applications, intended for use in cold climate.**

Construction product in accordance with applicable harmonised specifications:

**EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM
EN 15651-2:2012: Type G-CC: CLASS 25LM**

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 3
System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Silirub Color

Revision: 8/10/2014

Page 2 from 4

Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-2: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery	≥ 70%	
Secant modulus at 23°C (N/mm ²)	≤ 0.4	
Secant modulus at -20°C (N/mm ²)	≤ 0.6	
Secant modulus at -30°C (N/mm ²)	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Elongation at break	≥ 25%	
Resistance to compression (N/mm ²)	0.26	
Durability	Pass	

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
BE-2300 Turnhout, 8/10/2014

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 8/10/2014

Page 3 from 4



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 230010

EN 15651-1: 2012

EN 15651-2: 2012

Sealant for facade for interior and exterior application, intended for use in cold climate.

Sealant used for sealing glazing applications, intended for use in cold climate.

Soudal Silirub Color

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM

EN 15651-2:2012: Type G-CC: CLASS 25LM

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-2: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Elastic recovery	≥ 70%	
Secant modulus at 23°C (N/mm ²)	≤ 0.4	
Secant modulus at -20°C (N/mm ²)	≤ 0.6	
Secant modulus at -30°C (N/mm ²)	≤ 0.9	
Tensile properties at maintained extension	NF	
Tensile properties at maintained extension at -30°C	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Elongation at break	≥ 25%	
Resistance to compression (N/mm ²)	0.26	
Durability	Pass	

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 8/10/2014

Page 4 from 4